

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 254

IDENTITY: SCREEN CLEANER

Revision Date: 09/07/99

Section I

Manufacturer's Name:QUEST CHEMICAL CORP.
Address: 12255 FM 529
NORTHWOODS IND. PARK
HOUSTON
State: TX Zip Code:77041

Telephone Numbers:
Emergency:
800/255-3924
Information:
713/896-8188

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 0 HEALTH: 1 PERSONAL PROTECT: 1

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)

Table with 7 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, and %. Rows include 2-BUTOXY ETHANOL, ISOPROPYL ALCOHOL, and L.P.G.

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING
AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: N/A Specific Gravity (water=1) 0.98
Vapor Pressure(mm Hg) 17.5 Melting Point: N/A
Vapor Density(AIR=1) >1 Evaporation Rate: >1
Solubility in Water: 100% (Butyl Acetate=1)
Appearance and Odor: WHITE FOAM, MILD ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used):NONE Flammable Limits: LEL:N/A UEL: N/A
Extinguishing Media: STANDARD CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: NONE NEEDED

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO
TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 254

Stability: Unstable: Conditions to avoid:
Stable: X TEMPERATURES ABOVE 120 F
Incompatability (Materials to Avoid): NONE

Hazardous Decomposition or Byproducts: NONE

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion:NO
Health Hazards(Acute and Chronic):
INHALATION: EXCESSIVE AMOUNT MAY CAUSE SLIGHT DIZZINESS. EYES: IRRITATION
REDDENING. SKIN: MAY CAUSE LOCALIZED DRYING WITH EXCESSIVE EXPOSURE.

Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS ABOVE

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR.
EYES: FLUSH WITH RUNNING WATER FOR 15 MINUTES. SKIN: WASH COMPLETELY
WITH RUNNING WATER. CONTACT PHYSICIAN IF IRRITATION PERSISTS.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH
RAG OR SOME ABSORBENT CLAY MATERIAL. DISPOSE OF RESIDUE IN ACCORDANCE
WITH FEDERAL, STATE AND LOCAL GUIDELINES.

Waste Disposal Method: DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT
REUSE CONTAINER. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR
HEAT OR OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE
BURSTING.

Other Precautions: NONE

Section VIII: CONTROL MEASURES

Respiratory Protection: N/A
Ventilation: Local Exhaust:N/A
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves:N/A
Eye Protection: N/A
Other Protective Clothing or Equipment:
N/A
Work/Hygienic Practices:
N/A