THINK SAFE, WORK SAFE, BE SAFE

April 30, 2014 Volume 6, Issue 4



- Always follow correct procedures.
- Never take short cuts.
- Clean up your mess.
- Be alert and awake on the job.
- Be attentive to your surrounds.
- When in doubt contact your manager.
- Never take risks.
- Obey safety signs.
- Take short breaks.
 - Report near misses.

www.complianceandsafety.com



Can you identify the safety violations in this picture? Test Your Knowledge.



Answer: Lack of Eye and Face Protection, and Machine Guarding

KSU DIVISION OF FACILITIES



Working Safely in Trenches

Two workers are killed every month in trench collapses. Each worker in a trench shall be protected from a cave-in by an adequate protective system. Some of the protective systems for trenches are:

20000000

- Sloped for stability; or
- Cut to create stepped benched grades (Type A or B soil only); or
- Supported by a system made with materials such as posts, beams, shores or planking and hydraulic jacks; or
- Shielded by a trench box to protect workers in a trench.

Excavated or other materials and equipment must be at least 2 feet back from the edge of a trench; and

A safe way to exit must be provided within 25 feet of workers in a trench.

A competent person must inspect trenches daily and when conditions change. An unprotected trench is an early grave. Do not enter an unprotected trench.



SHA 32 43-09R-11

2' or more